

Applicant: Schleth, et al.
Application Serial No.: 10/622,041
Filing Date: July 17, 2003
Docket No.: 442-192
Page 2

IN THE SPECIFICATION:

On page 1, after the title, but before paragraph [0001], please insert the following:

FIELD OF THE INVENTION

On page 1, before paragraph [0002], please insert the following new heading:

BACKGROUND OF THE INVENTION

On page 2, before paragraph [0004], please insert the following new heading:

SUMMARY OF THE INVENTION

On page 5, before paragraph [0015], please insert the following new heading:

BRIEF DESCRIPTION OF THE DRAWINGS

On page 7, before paragraph [0024], please insert the following new heading:

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

On page 9, please amend paragraph [0033] as follows:

[0033] As well shown in FIGS. 5 through 7, each annular groove has an axially aligned groove floor 52 and two radially opposite inner and outer groove flanks 53 and 54. The sealing body 16 has a foot section 26 thereof placed in the associated annular groove 25 and extends--as seen in the initial position in accordance with FIGS. 1, 8 and 5--at a sealing bead

Applicant: Schleth, et al.
Application Serial No.: 10/622,041
Filing Date: July 17, 2003
Docket No.: 442-192
Page 3

24 through the groove opening 55 axially from the annular groove 25 and accordingly projects past the principal body 16 15 in an axial direction.